

MOLDEX

SPILL CLEAN UP METHODS

Stop leak if possible without risk. Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate. Do not contaminate water sources or sewer. Absorb in vermiculite, dry sand or earth and place into containers. Wash thoroughly after dealing with a spillage.

7 HANDLING AND STORAGE

USAGE PRECAUTIONS

Avoid spilling, skin and eye contact. Keep away from heat, sparks and open flame. Ventilate well, avoid breathing vapours. Use approved respirator if air contamination is above accepted level. Container must be kept tightly closed. Use explosion proof electric equipment.

STORAGE PRECAUTIONS

Keep away from heat, sparks and open flame. Keep containers tightly closed. Keep in original container.

STORAGE CLASS

Flammable liquid storage.

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Name	Std	LT - ppm	LT - mg/m3	ST - ppm	ST - mg/m3
PROPAN-2-OL	WEL	400 ppm	999 mg/m3	500 ppm	1250 mg/m3

PROTECTIVE EQUIPMENT



ENGINEERING MEASURES

Provide adequate general and local exhaust ventilation.

RESPIRATORY EQUIPMENT

Respiratory protection must be used if air contamination exceeds acceptable level.

HAND PROTECTION

Use protective gloves.

EYE PROTECTION

Wear splash-proof eye goggles to prevent any possibility of eye contact.

OTHER PROTECTION

Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact.

HYGIENE MEASURES

DO NOT SMOKE IN WORK AREA! Wash at the end of each work shift and before eating, smoking and using the toilet. Wash promptly with soap & water if skin becomes contaminated. Promptly remove any clothing that becomes contaminated. When using do not eat, drink or smoke.

9 PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE	Clear Liquid	RELATIVE DENSITY	.910-.920 @ 20 °c
COLOUR	Straw	VAPOUR PRESSURE	33 mmHg @ 20 °c
ODOUR	Mild (or faint). Rubbing alcohol.	VOLATILE BY VOL. (%)	95
VOLATILITY DESCRIPTION	Volatile.	FLAMMABILITY LIMIT - LOWER(%)	2
SOLUBILITY	Soluble in water		
BOILING POINT (°C)	81-83 760 mm Hg		
VAPOUR DENSITY (air=1)	>1		
EVAPORATION RATE	>1 BuAc=1		
FLASH POINT (°C)	56 CC (Closed cup).		
FLAMMABILITY LIMIT - UPPER(%)	12		

10 STABILITY AND REACTIVITY

STABILITY

Stable under normal temperature conditions.

CONDITIONS TO AVOID

Avoid heat, flames and other sources of ignition. Avoid contact with strong reducing agents.

MOLDEX

MATERIALS TO AVOID

Strong oxidising substances.

HAZARDOUS DECOMPOSITION PRODUCTS

Fire creates: Vapours/gases/fumes of: Carbon monoxide (CO). Carbon dioxide (CO2).

11 TOXICOLOGICAL INFORMATION

HEALTH WARNINGS

INHALATION. May cause irritation to the respiratory system. SKIN CONTACT. Acts as a defatting agent on skin. May cause cracking of skin, and eczema. EYE CONTACT. May cause severe irritation to eyes. INGESTION. May cause stomach pain or vomiting.

12 ECOLOGICAL INFORMATION

ECOTOXICITY

Not known.

13 DISPOSAL CONSIDERATIONS

DISPOSAL METHODS

Dispose of waste and residues in accordance with local authority requirements.

14 TRANSPORT INFORMATION



UK ROAD CLASS	3		
PROPER SHIPPING NAME	ISOPROPANOL (ISOPROPYL ALCOHOL)		
UN NO. ROAD	1219	UK ROAD PACK GR.	II
ADR CLASS NO.	3	ADR CLASS	Class 3: Flammable liquids.
ADR PACK GROUP	II	HAZARD No. (ADR)	33
ADR LABEL NO.	3	HAZCHEM CODE	2YE
CEFIC TEC(R) NO.	30GF1-I-II	RID CLASS NO.	3
RID PACK GROUP	II	UN NO. SEA	1219
IMDG CLASS	3	IMDG PAGE NO.	3
IMDG PACK GR.	II	EMS	F-E, S-D
MFAG	See Guide	MARINE POLLUTANT	No.
UN NO. AIR	1219	AIR CLASS	3
AIR PACK GR.	II		

15 REGULATORY INFORMATION

LABELLING



Irritant



Highly Flammable

RISK PHRASES

R67	Vapours may cause drowsiness and dizziness.
R11	Highly flammable.
R36	Irritating to eyes.

SAFETY PHRASES

S9	Keep container in a well-ventilated place.
S16	Keep away from sources of ignition - No smoking.
S25	Avoid contact with eyes.

MOLDEX

S26	In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
S37	Wear suitable gloves.
S51	Use only in well-ventilated areas.
S1/2	Keep locked up and out of the reach of children.
S60	This material and its container must be disposed of as hazardous waste.
P11	Restricted to professional users.

UK REGULATORY REFERENCES

Highly Flammable Liquid Regulations 1972. Petroleum (Consolidation) Act, as amended 1984 SI 1244.

EU DIRECTIVES

Dangerous Preparations Directive 1999/45/EC. System of specific information relating to Dangerous Preparations. 2001/58/EC.

STATUTORY INSTRUMENTS

Chemicals (Hazard Information and Packaging) Regulations.

APPROVED CODE OF PRACTICE

Safety Data Sheets for Substances and Preparations. Classification and Labelling of Substances and Preparations Dangerous for Supply.

GUIDANCE NOTES

Workplace Exposure Limits EH40. CHIP for everyone HSG(108).

16 OTHER INFORMATION

REVISION DATE May 2007

RISK PHRASES IN FULL

R11	Highly flammable.
R22	Harmful if swallowed.
R36	Irritating to eyes.
R67	Vapours may cause drowsiness and dizziness.

DISCLAIMER

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.