

PENETRATING DRYENE

7 HANDLING AND STORAGE

USAGE PRECAUTIONS

Keep away from heat, sparks and open flame. Avoid spilling, skin and eye contact. Provide good ventilation. Avoid inhalation of vapours.

STORAGE PRECAUTIONS

Flammable/combustible - Keep away from oxidisers, heat and flames. Store in tightly closed original container in a dry, cool and well-ventilated place. Keep in original container.

STORAGE CLASS

Flammable liquid storage.

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Name	Std	LT - ppm	LT - mg/m3	ST - ppm	ST - mg/m3
METHANOL	WEL	200 ppm(Sk)	266 mg/m3(Sk)	250 ppm(Sk)	333 mg/m3(Sk)
OXALIC ACID	OES		1 mg/m3		2 mg/m3

INGREDIENT COMMENTS

WEL = Workplace Exposure Limits

PROTECTIVE EQUIPMENT



ENGINEERING MEASURES

Well-ventilated area.

HAND PROTECTION

Use protective gloves.

EYE PROTECTION

Use eye protection.

OTHER PROTECTION

Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact.

HYGIENE MEASURES

DO NOT SMOKE IN WORK AREA! Wash at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. Wash promptly with soap & water if skin becomes contaminated. Use appropriate skin cream to prevent drying of skin. When using do not eat, drink or smoke.

9 PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE	Liquid Clear	RELATIVE DENSITY	.860 @ 20 °c
COLOUR	Colourless	VAPOUR PRESSURE	98 mmHg @ 20 °c
ODOUR	Odour of alcohol Mild (or faint).	FLASH POINT (°C)	11 CC (Closed cup).
SOLUBILITY	Soluble in water	FLAMMABILITY LIMIT - UPPER(%)	36.5
BOILING POINT (°C)	67-69 760 mm Hg		
VAPOUR DENSITY (air=1)	>1		
EVAPORATION RATE	>1 BuAc=1		
FLAMMABILITY LIMIT - LOWER(%)	6		

10 STABILITY AND REACTIVITY

STABILITY

Stable under normal temperature conditions.

CONDITIONS TO AVOID

Avoid heat, flames and other sources of ignition. Avoid contact with acids and alkalis. Avoid contact with strong oxidisers. Avoid contact with strong reducing agents.

11 TOXICOLOGICAL INFORMATION

PENETRATING DRYENE

INHALATION

Toxic by inhalation. Prolonged inhalation of high concentrations may damage respiratory system. May cause irritation to the respiratory system. High concentrations of vapours may irritate respiratory system and lead to headache, fatigue, nausea and vomiting.

INGESTION

Toxic if swallowed. Causes burns. May cause discomfort if swallowed. May cause stomach pain or vomiting. Swallowing concentrated chemical may cause severe internal injury.

SKIN CONTACT

Toxic in contact with skin. Causes burns. Prolonged contact may cause dryness of the skin.

EYE CONTACT

Causes burns. Contact with concentrated chemical may very rapidly cause severe eye damage, possibly loss of sight.

HEALTH WARNINGS

Prolonged inhalation of high concentrations may damage respiratory system. Prolonged or repeated exposure may cause severe irritation.

The product causes irritation of mucous membranes and may cause abdominal discomfort if swallowed.

12 ECOLOGICAL INFORMATION

ECOTOXICITY

Not known.

13 DISPOSAL CONSIDERATIONS

DISPOSAL METHODS

Dispose of waste and residues in accordance with local authority requirements.

14 TRANSPORT INFORMATION



UK ROAD CLASS	3		
PROPER SHIPPING NAME	METHANOL		
UN NO. ROAD	1230	UK ROAD PACK GR.	II
ADR CLASS NO.	3	ADR CLASS	Class 3: Flammable liquids.
ADR PACK GROUP	II	HAZARD No. (ADR)	336
ADR LABEL NO.	3 & 6.1	HAZCHEM CODE	2WE
CEFIC TEC(R) NO.	30GFT1-II	RID CLASS NO.	3
RID PACK GROUP	II	UN NO. SEA	1230
IMDG CLASS	3	IMDG PAGE NO.	3 & 6.1
IMDG PACK GR.	II	EMS	F-E, S-D
MFAG	19	MARINE POLLUTANT	No.
UN NO. AIR	1230	AIR CLASS	3
AIR SUB CLASS	6.1	AIR PACK GR.	II

15 REGULATORY INFORMATION

LABELLING



Toxic



Highly Flammable

CONTAINS

METHANOL
OXALIC ACID

RISK PHRASES

R23/24/25 Toxic by inhalation, in contact with skin and if swallowed.

PENETRATING DRYENE

R39/23/24/25	Toxic: danger of very serious irreversible effects through inhalation, in contact with skin and if swallowed.
R11	Highly flammable.
SAFETY PHRASES	
S9	Keep container in a well-ventilated place.
S16	Keep away from sources of ignition - No smoking.
S27	Take off immediately all contaminated clothing.
S38	In case of insufficient ventilation, wear suitable respiratory equipment.
S45	In case of accident or if you feel unwell, seek medical advice immediately (show label where possible).
S36/37	Wear suitable protective clothing and gloves.
S1/2	Keep locked up and out of the reach of children.
S60	This material and its container must be disposed of as hazardous waste.
P11	Restricted to professional users.

ENVIRONMENTAL LISTING

Rivers (Prevention of Pollution) Act 1961. Control of Pollution (Special Waste Regulations) Act 1980.

EU DIRECTIVES

System of specific information relating to Dangerous Preparations. 2001/58/EC.

STATUTORY INSTRUMENTS

Chemicals (Hazard Information and Packaging) Regulations.

APPROVED CODE OF PRACTICE

Classification and Labelling of Substances and Preparations Dangerous for Supply.

GUIDANCE NOTES

Workplace Exposure Limits EH40. Introduction to Local Exhaust Ventilation HS(G)37. CHIP for everyone HSG(108).

16 OTHER INFORMATION

INFORMATION SOURCES

Dangerous Properties of Industrial Materials Report, N.Sax et al.

REVISION DATE

May 2007

RISK PHRASES IN FULL

R11	Highly flammable.
R21/22	Harmful in contact with skin and if swallowed.
R23/24/25	Toxic by inhalation, in contact with skin and if swallowed.
R39/23/24/25	Toxic: danger of very serious irreversible effects through inhalation, in contact with skin and if swallowed.

DISCLAIMER

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.